

14/7/1

DIALOG(R) File 351:Derwent WPI

(c) 2002 Derwent Info Ltd. All rts. reserv.

007435609

WPI Acc No: 1988-069544/ 198810

Ammonium fluoride prodn. - by continuous neutralisation of hydrofluoric acid with ammonia gas in two-stage system

Patent Assignee: DNEPR CHEM TECHN INST (DNCH)

Inventor: ANISIMOV A P; LOSEV V G; MINYAILO Y U G

Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No	Kind	Date	Applicat No	Kind	Date	Week
SU 1326552	A	19870730	SU 3809191	A	19840828	198810 B

Priority Applications (No Type Date): SU 3809191 A 19840828

Patent Details:

Patent No	Kind	Lan Pg	Main IPC	Filing Notes
SU 1326552	A	2		

Abstract (Basic): SU 1326552 A

NH₄F used in chem industry is made by neutralising HF soln. with NH₃ at 50-70 deg. C. Better yields are secured by using 2-stage mfg. Stage 1 is conducted with a 3-5% deficiency of the stoichiometric amt. of NH₃. In stage 2, the remaining NH₃ is added and the temp. raised to 95-105 deg. C.

21.6% HF is run into a graphite-plastic reactor, while NH₃ gas is pumped in simultaneously at 4.35l/min. The intense heat of reaction is removed by cooling water, so that the temp. does exceed 50 deg. C. In a second polymeric compartment NH₃ is supplied at 0.135 l/min. while the cooling water ensures that the exit temp. is below 95 deg. C. Prod. analysis is conducted at intervals and a typical analysis shows (wt. %): NH₄F 39.85, NH₃ 0.45, Fe, Cu, Ni Mn, Pb only minute traces. The yield is 99.8%.

ADVANTAGE - The patented process gives NH₄F in 99.9% yield; metallic impurities are less than 1.10 power minus 5. The use of a

2-stage process minimises plant corrosion problems and allows continuous operation. Bul.28/30.7.87.

Dwg.0/0

Derwent Class: E35

International Patent Class (Additional): C01C-001/16

?s pn=fr 1596497

S15 1 PN=FR 1596497

?t 15/7

15/7/1

DIALOG(R) File 351:Derwent WPI

(c) 2002 Derwent Info Ltd. All rts. reserv.